

EFFICIENCY 14 SEER HEAT PUMP ENVIRONMENTALLY SOUND R-410A REFRIGERANT

1½ THRU 5 TONS SPLIT SYSTEM

208 / 230 Volt, 1-phase, 60 Hz

REFRIGERATION CIRCUIT

- Scroll compressors on all models
- Suction line accumulator factory installed
- Integrated solid state control with Time-Temperature Defrost
- High and low pressure switches
- Copper tube / aluminum fin coil

EASY TO INSTALL AND SERVICE

- Easy access service valves on all models
- External high and low refrigerant service ports
- Only two screws to access control panel
- Factory charged with R-410A refrigerant

BUILT TO LAST

- Painted cabinet finish over galvanized steel
- Models available with coated inlet grille with 2" (51mm) spacing and with 3/8" (10mm) grille spacing for extra protection

WARRANTY*

- 5 year compressor limited warranty (including compressor and coil)
 - With timely registration, an additional 5 year parts limited warranty (including compressor and coil)

* For residential applications only. See warranty certificate for complete details and restrictions, including warranty coverage for other applications.



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.

UNIT PERFORMANCE DATA							
Model Number	Size (tons)	Nominal Btu/hr	Min. Circuit Ampacity	Max. Fuse or Breaker	Operating Dimensions length x width x height in. (mm)	Operating/Ship Weight lbs. (kg)	Notes
R4H418AKB R4H418GKB	1½	18,000	11.8	20	23-1/8 x 23-1/8 x 35-1/4 (587 x 587 x 899)	136/166 (61/75)	
R4H424AKB R4H424GKB	2	24,000	14.2	25	25-3/4 x 25-3/4 x 35-1/4 (654 x 654 x 895)	144/175 (65/79)	
R4H430AKB R4H430GKB	2½	30,000	16.9	30	31-3/16 x 31-3/16 x 31-13/16 (792 x 792 x 808)	158/180 (72/82)	
R4H436AKB R4H436GKB	3	36,000	20	30	31-3/16 x 31-3/16 x 28-7/16 (792 x 792 x 722)	170/201 (77/91)	
R4H442AKB R4H442GKB	3½	42,000	24	40	31-3/16 x 31-3/16 x 39-1/8 (792 x 792 x 994)	201/235 (91/107)	
R4H448AKB R4H448GKB	4	48,000	25.2	40	31-3/16 x 31-3/16 x 28-7/16 (792 x 792 x 722)	197/232 (89/105)	
R4H460AKB R4H460GKB	5	60,000	32	50	31-3/16 x 31-3/16 x 31-13/16 (792 x 792 x 808)	212/248 (96/113)	